





Process for preparing transparent casting resins.






Patent number: EP0039017
Publication date: 1981-11-04
Inventor: REEH ULRIKE; DENK HANS DR
Applicant: SIEMENS AG (DE)
Classification:
- **international:** C08G59/42; C08G59/24; C08G59/68
- **europaean:** H01L33/00B2D, C08G59/42, C08G59/42Y, C08G59/68G
Application number: EP19810102961 19810416
Priority number(s): DE19803016103 19800425

Also published as:

 US4365052 (A1)
 JP56167724 (A)
 GB2074579 (A)
 EP0039017 (A3)
 DE3016103 (A1)

more >>

Cited documents:

 US3340212
 DE2642465
 US3689444
 CH546806
 DE2254487
more >>

Abstract not available for EP0039017
Abstract of correspondent: **US4365052**

The invention relates to a method for the manufacture of transparent casting resins. According to the invention, a liquid acid anhydride (b) is admixed to a premixture (a), which is liquid at room temperature, of zinc octoate, a low-molecular weight acid ester and, optionally, an organic phosphite, and this mixture of (a) and (b) is added, preferably at temperatures ≤ 50 DEG C., to liquid aromatic diglycidyl ethers. Diphenyldecyl phosphite is particularly well suited as an organic phosphite. The casting resins obtained are transparent and find use particularly for casting-in and encapsulating opto-electronic components such as light-emitting diodes (and diode displays), photo diodes and photo transistors.

Data supplied from the esp@cenet database - Worldwide

BEST AVAILABLE COPY